

## Premises Raceway

### Flame Retardant/HDPE/Corrugated Fiber Raceway



#### Features:

- \* 1" & 1 1/4" available in stock
- \* Suitable for most riser applications
- \* Flammability equals UL 94 V-O
- \* Not UL Listed
- \* Custom lengths available



Petroflex offers HDPE corrugated Fire Retardant conduit in 1" and 1 1/4" sizes suitable for most Riser applications. Petroflex Fire Retardant is chemically inert to most acids, aliphatic and aromatic organic compounds, chlorinated solvents, and alcohols. Fire Retardant also has excellent mechanical properties over a wide range of temperatures as well as being abrasion resistant with a relatively low coefficient of friction. Standard and custom lengths are available and all lengths come with factory installed 1130# pull tape. Petroflex HDPE Fire Retardant is not UL Listed.

<u>Size</u>	<u>Part #</u>	<u>Min. I.D.</u>	<u>Nom. O.D.</u>	<u>Mean Wall</u>	<u>Weight lbs./ft</u>
1.00"	PC100FR	1.00"	1.300"	0.040	0.0816
1.25"	PC125FR	1.25"	1.540"	0.040	0.1022

**\*R prefix to any part # indicates cut-to-length & does not change fit, form or function (i.e. RPC100FR, RPC125FR)**

#### Standard Reel Lengths:

<u>Size</u>	<u>Length</u>	<u>Reel Size</u>	<u>Wgt./lbs.</u>	<u>Availability</u>
1.00"	250'	Coil	26	Recoil
1.00"	500'	38"x22"	65	Recoil
1.00"	1000'	38"x43"	108	Recoil
1.00"	2000'	44"x43"	192	Recoil
1.00"	4500'	60"x45"	478	Recoil
1.00"	7000'	72"x45"	707	Stock
1.25"	200'	Coil	31	Recoil
1.25"	500'	44"x22"	77	Recoil
1.25"	1000'	44"x43"	130	Recoil
1.25"	1500'	48"x45"	254	Recoil
1.25"	2500'	60"x45"	366	Recoil
1.25"	4500'	72"x45"	595	Stock